

# CitoShelf™



Illuminated shelving system for use with CitoHolder system



Description	Standard	Optional
<b>Applications</b>		
Protection class	Low voltage	
Body material	Fibreboard, polycarbonate	
IP rating	IP44	
Type of connection	Ball bearing	
<b>Electric data</b>		
Wattage	4W	4W, 8W
Frequency	n/a	n/a
Voltage	12V, DC	24V
Current	0.33A	0.17-0.33A
<b>Light Source (LED strip)</b>		
Colour	4000K	3000K, 5700K
Luminous flux	420 lm	360 lm, 460 lm
Angle	175°	175°
Life	Up to 100,000 h	
<b>Shelf Geometries</b>		
Length/Width	688 mm	1380 mm
Depth	250 mm	250 mm
Height/thickness	8.4 mm	10.4 mm
<b>Type depending on connection side</b>		
Model	Left or right	
<b>Code – part number</b>		
order	CS7-L, CS7-R	
EAN	5901549416510	
<b>Packaging unit (per 1 unit)</b>		
Dimensions	688/250/8.4	
Weight	1.75 kg	
Volume		
<b>Folding cardboard box (per 5 units)</b>		
Dimensions	740/300/100	
Weight	9.7 kg	
Volume	22 dcm <sup>3</sup>	

## CONTINUOUS PRODUCT DEVELOPMENT

All our Suppliers and Manufacturers have a policy of continuous product development so that new standards and regulations can be met as they are introduced. For this reason we must reserve the right to alter specifications without notice and products will sometimes be supplied with modifications which do not strictly comply with illustrations or descriptions given.